

	Description of Item	Unit	DRUK GENERAL ENTERPRIS E	Tenzin Norgyel Tshongkhang
1	(Bosch 108 Pieces All-in-One Metal Hand Tool Kit. 2607002790) 9 Screwdriver Bits. 6 Hexagon Socket Wrenches. 8 Precision Bits. 2 Adaptors. 1 Ratchet Hand Screwdrivers. 8 Allen Keys. 3 Masonry Drill Bits. 30 S-Plugs. 30 Screws. Flat-nose Pliers. Combination Pliers. 1 Tester. 1 Hammer. Cutter. Measuring Tape 3m. 1 Insulation Tape. 1 Torch. 1 Wrench. 1 Handsaw	set	4585	9500
2	1 /2inch GI Nipple Length is 10 cm Tolerance +0 cm. -2 cm. IS 1879-1986 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	11.6	20
3	1 /2inch GI Sockets IS 1879- 1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	30.8	30
4	1 1/2 inch GI Elbow IS 1879- 1987(BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	197.12	40
5	1 1/2 inch GI Nipple Length is 10 cm Tolerance +0 cm. -2 cm. IS 1879-1986 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	43.5	85
6	1 1/2 inch GI Sockets IS 1879- 1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	144.32	75
7	1 1/2 inch GI Unions IS 1879- 1992 (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	433.6	245

8	1 1/2inch - Brass Globe Valve Class I. 1.5 MPa IS 778-84 (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	1704	0
9	1 1/2inch Float Valve Copper or bras made. Min. wt +20gms. -0gm See attached drawing for detail specification. (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	3655	3500
10	1 1/2inch GI pipe. Medium duty IS 1239/90 longitudinally welded mild steel. hot dipped galvanised as per IS 4736/68. both ends male threads BS 21 and greased. Socket IS 1239/92 mild steel galvanised and chamfered. Socketed on one end and other end covered with heavy duty HDP thread protector. Length 6.00m.. Tolerance +15cm & -0cm.(BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	mtr	369.75	467
11	1 1/2inch x 1inch GI Reducers IS 1879-1990 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	161.6	120
12	1 1/2inchx1 1/2inch x 1/2inch Unequal Tee IS 1879-1992 (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	308.8	155
13	1 inch GI Nipple Length is 10 cm Tolerance +0 cm. -2 cm. IS 1879-1986 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	19.2	25
14	1 inch GI Sockets IS 1879- 1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	66.88	40
15	1 inch GI Tee's equal IS 1879-1992 (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	121.44	60

16	1 inch GI Unions IS 1879-1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	211.2	70
17	1/2 inch GI Elbow IS 1879- 1987 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	33.79	40
18	1/2 inch GI Tee's equal IS 1879-1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	54.4	40
19	1/2 inch GI Unions IS 1879- 1992 (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	99.2	45
20	1/2inch - Brass Globe Valve Class I. 1.5 MPa IS 778-84 (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	465.6	0
21	1/2inch - Tapstand Regulating Valve set Class I. 1.5 MPa IS 778-84 (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	576	750
22	1/2inch Float Valve Copper or bras made. Min. wt ...+20gms. - 0gm See attached drawing for detail specification. (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	1455	2300
23	1/2inch GI pipe. Medium duty IS 1239/90 longitudinally welded mild steel. hot dipped galvanised as per IS 4736/68. both ends male threads BS 21 and greased. Socket IS 1239/92 mild steel galvanised and chamfered. Socketed on one end and other end covered with heavy duty HDP thread protector. Length 6.00m.. Tolerance +15cm & - 0cm.(BSB approved brands/jindal or equivalent. need to submit the sample and manufacturere's certificate of origin)	mtr	143.55	210
24	1/2inch Valve box key with 3 points (submit the sample)	Each	1950	1500

25	1 1/2 inch GI Tee's equal IS 1879-1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	270.4	110
26	1 1/2 inch - Brass Gate Valve. GM full way valve. Class I. 1.5 MPa IS 778-84 (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	2036.8	1700
27	1 1/2 inch Valve box key with 3 points (submit the sample)	Each	0	1500
28	110 mm x 4 inch Flange set IS 4984/87 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	915	600
29	1 inch - Brass Gate Valve. GM full way valve. Class I. 1.5 MPa IS 778-84 (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	1009.5	1200
30	1 inch - Brass Globe Valve Class I. 1.5 MPa IS 778-84 (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	738	0
31	1 inch Float Valve Copper or brass made. Min. wt ... +20gms. - 0gm See attached drawing for detail specification. (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	1795.5	2900
32	1 inch GI Elbow IS 1879-1987 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	89.1	60
33	1 inch GI pipe. Medium duty IS 1239/90 longitudinally welded mild steel. hot dipped galvanised as per IS 4736/68. both ends male threads BS 21 and greased. Socket IS 1239/92 mild steel galvanised and chamfered. Socketed on one end and other end covered with heavy duty HDP thread protector. Length 6.00m.. Tolerance +15cm & -0cm. (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	mtr	250.85	300

34	1 inch x 1/2 inch GI Reducers IS 1879-1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	105.85	70
35	1 inch x 1 inch x 1/2 inch Unequal Tee IS 1879-1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	147.2	80
36	2 inch GI Elbow IS 1879-1987 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	300.8	180
37	2 inch GI Nipple Length is 10 cm Tolerance +0 cm. -2 cm. IS 1879- (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	64	80
38	2 inch GI Sockets IS 1879- 1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	230.4	80
39	2 inch GI Tee's equal IS 1879-1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	457.6	160
40	2 inch GI Unions IS 1879-1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	636.8	270
41	2 1/2 inch Valve box with endcap GI pipe of medium duty. Burrs removed. cutted edges smoothened with file or grinder. GI-thread is clean. smooth and greased. Endcap and pipe screwed together.(BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	Each	1990	0
42	2 inch - Brass Gate Valve. GM full way valve. Class I. 1.5 MPa IS 778-84 (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	3233.6	2550

43	2inch Float Valve Copper or bras made. Min. wt +20gms. - 0gm See attached drawing for detail specification. (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	4320	3700
44	2inch GI pipe. Medium duty IS 1239/90 longitudinally welded mild steel. hot dipped galvanised as per IS 4736/68. both ends male threads BS 21 and greased. Socket IS 1239/92 mild steel galvanised and chamfered. Socketed on one end and other end covered with heavy duty HDP thread protector. Length 6.00m.. Tolerance +15cm & -0cm. (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	mtr	561.6	635
45	2inch Valve box key with 3 points (submit the sample)	Each	0	2500
46	2inch x 1 1/2inch GI Reducers IS 1879-1989(BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	259.2	115
47	2inchx2inch x 1/2inch Unequal Tee IS 1879-1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	513.6	165
48	3 inch GI Elbow IS 1879- 1987(BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	876.48	450
49	3 inch GI Endcaps with 16M nut IS 1879-1987 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	147.2	480
50	3 inch GI Nipple Length is 10 cm Tolerance +0 cm. -2 cm. IS 1879-1987 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	112	210
51	3 inch GI Sockets IS 1879- 1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	573.76	320

52	3 inch GI Tee's equal IS 1879-1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	1089.6	390
53	3 inch GI Unions IS 1879-1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	1648	750
54	3inch - Brass Gate Valve. GM full way valve. Class I. 1.5 MPa IS 778-84 (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	6753.6	6600
55	3inch GI pipe. Medium duty IS 1239/90 longitudinally welded mild steel. hot dipped galvanised as per IS 4736/68. both ends male threads BS 21 and greased. Socket IS 1239/92 mild steel galvanised and chamfered. Socketed on one end and other end covered with heavy duty HDP thread protector. Length 6.00m.. Tolerance +15cm & - 0cm.(BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	mtr	841	1095
56	3inchx3inch x 1/2inch Unequal Tee IS 1879-1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	1126.4	680
57	4 inch GI Elbow IS 1879-1987 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	1507.2	510
58	4 inch GI Endcaps with 16M nut IS 1879-1987 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	248	580
59	4 inch GI Nipple Length is 10 cm Tolerance +0 cm. -2 cm. IS 1879-1987 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	160	300

60	4 inch GI Sockets IS 1879- 1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	1025.6	600
61	4 inch GI Tee's equal IS 1879-1992 (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	2040	600
62	4 inch GI Unions IS 1879-1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	2576	850
63	4inch - Brass Gate Valve. GM full way valve. Class I. 1.5 MPa IS 778-84 (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	13640	13500
64	4inch GI pipe. Medium duty IS 1239/90 longitudinally welded mild steel. hot dipped galvanised as per IS 4736/68. both ends male threads BS 21 and greased. Socket IS 1239/92 mild steel galvanised and chamfered. Socketed on one end and other end covered with heavy duty HDP thread protector. Length 6.00m.. Tolerance +15cm & -0cm. (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	mtr	1404.8	1740
65	4inch Valve box with endcap GI pipe of medium duty. Burrs removed. cutted edges smoothened with file or grinder. GI-thread is clean. smooth and greased. Endcap and pipe screwed together.(BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	Each	2990	3200
66	4inch x 3inch GI Reducers IS 1879-1987 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	1062.24	600
67	4inchx4inch x 1/2inch Unequal Tee IS 1879-1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	2108.8	810

68	50 mm x 1 1/2 inch Flange set IS 4984/87(BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	472.5	350
69	63 mm x 2 inch Flange set IS 4984/87 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	607.5	455
70	90 mm x 3inch Flange set IS 4984/87 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin).	each	765	490
71	Abney level	each	2550	28000
72	Air release Valve 1/2inch (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	each	1363.2	1650
73	Altimeter	each	6000	10500
74	ATI CPVC Heavy duty pipe cutter capacity (63mm, Green)	no	0	3850
75	Barbed wire Gauge 12 SWG double wired. double barbed 90 degrees angle. every 10 cm. galvanized (IS- 278/1969). In roll of 30 kg weight tolerance +3 kg. -0 kg(BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	30kg)R	2847	3000
76	Bosch Electrician Kit GSB 550	each	7700	9500
77	Bosch GLM 100-25 C 100-meter laser distance meter with inbuilt camera	no	31479	35000
78	Bosh GSB 500W drill machine set, (1 500W hammer drill, 1 Measuring tape, 10 screwdriver bit, 30 screw and plugs, 4 Metal drill bit, 1 Claw hammer, 8 Socket wrench, 1 adjustable knife, 1 Screw bit holder, 5 wood drill bit, 5 Masonry drill bit, 1 combination plier, 1 Adjustable wrench, 1 spirit level, 1 key chuck.	Set	5880	9800
79	Brass bib 15mm dia(Heay Duty-BSB approved brand)	each	475.2	350
80	Brass stop cock 15mm dia(Heay Duty-BSB approved brand)	each	475.2	550
81	Brass Union. 20 mm x 1/2inch SP-57-1993(BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	264	450

82	Brass Union. 32 mm x 1inch SP-57-1993 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	593.6	650
83	Brass Union. 50 mm x 1 1/2inch SP-57-1992 (BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	1156.8	950
84	Brass Union. 63 mm x 2inch SP-57-1991(BSB approved brands/jindal or equivalent. need to submit the sample and manufacturer's certificate of origin)	each	1310.4	1320
85	BULLDOG GRIP (10 mm)	each	255	300
86	BULLDOG GRIP (13 mm)	each	285	350
87	BULLDOG GRIP (16 mm)	each	360	400
88	BULLDOG GRIP (20 mm)	each	480	650
89	BULLDOG GRIP (26 mm)	each	585	600
90	BULLDOG GRIP (3 mm)	each	120	300
91	BULLDOG GRIP (32 mm)	each	660	700
92	BULLDOG GRIP (6 mm)	each	195	300
93	BULLDOG GRIP (8 mm)	each	255	300
94	CABLE (WIRE ROPE) (10 mm)	mtr	270	0
95	CABLE (WIRE ROPE) (13 mm)	mtr	420	0
96	CABLE (WIRE ROPE) (16 mm)	mtr	585	0
97	CABLE (WIRE ROPE) (20 mm)	mtr	885	0
98	CABLE (WIRE ROPE) (26 mm)	mtr	1035	0
99	CABLE (WIRE ROPE) (3 mm)	mtr	135	0
100	CABLE (WIRE ROPE) (32 mm)	mtr	1492.5	0
101	CABLE (WIRE ROPE) (6 mm)	mtr	255	0
102	CABLE (WIRE ROPE) (8 mm)	mtr	315	0
103	Cantilever tools box three compartment	each	0	0
104	COMPOUND, PIPE JOINING	pot	0	600
105	CP Brass bib cock 15mm dia(Heay Duty-BSB approved brand)	each	657.6	650
106	CP Brass stop cock 15mm dia(Heay Duty-BSB approved brand)	each	657.6	650
107	Die bit 2inch for ratchet die set (submit sample)	each	1392	1200

108	Die bit 3inch for ratchet set (submit sample)	each	1948.8	2200
109	Die bit 4inch for ratchet die set (submit sample)	each	3619.2	3700
110	Double Blade. hacksaw single side IS 2594-1976(submit the sample)	each	16.64	20
111	Garmin GPSMAP 64SXGPS	each	0	60500
112	GREASE 1/2 kg	pot	350	0
113	Hacksaw frame	each	192	450
114	Hammer. Mason 1/2 kg	each	152	450
115	Hammer. sledge 1 kg	each	236.8	350
116	Hand/angle Grinder (BOSCH GWS 060)	each	3290	4500
117	HDPE Pipe cutter round 100-168mm (SOLWET Brand)	no	0	0
118	Heating Plate. 100 mm dia & 15mm (submit the sample)	each	960	2900
119	Heating Plate. 125 mm dia & 20mm (submit the sample)	each	1080	3500
120	HEMP	bdle	224	0
121	Hessian jute. 7.5 oz width 90cm. In roll of 30 meter.	Mtr	0	0
122	HTC Analog Altimeter AL-7000, (NAAFIE brand) Features; Meters (m)/Hpa. Technical data; basic function AL-7000 measuring range 0-5000m/580-1040 resolution 20m/5hpa operating temperature-20 degree Celsius-+60 storage condition-30'C; 90%R	no	0	0
123	line and point laser level. GLL 1P	each	0	0
124	Measuring tape(30) (submit the sample. Bosch brand)	each	280	500
125	Measuring tape(50mtr) (submit the sample. Bosch brand)	each	476	800
126	Measuring tape(5mtr) (submit the sample. Bosch brand)	each	119	150
127	Nails - U. 8 SWG H=35 mm. W=10 mm Sharpened	Kg	117	150
128	Nails 2inch Galvanised wire nails sharpened	kg	85.8	95
129	Nails 3inch Galvanised wire nails sharpened	kg	85.8	95
130	Nails 4inch Galvanised wire nails sharpened	Kg	85.8	95
131	Pipe chain vice 3inch (Ludra brand)	each	1144	4500
132	Pipe chain vice 4inch (Ludra brand)	each	1579.2	5100
133	Pipe chain vice 6inch (Ludra brand)	each	3030.4	6200
134	Pipe chain wrench for heavy duty 36inch (submit sample)	each	19350.4	0
135	Pipe chain wrench for heavy duty 48inch (submit sample)	each	25814.4	0

136	Pliers 8inch (submit the sample)	each	261	350
137	Portable vice set- 1/2inch to 2inch with stand (submit sample)	each	2227.2	0
138	Portable vice set- 3inch to 4inch with stand (submit sample)	each	3499.2	0
139	Prefab manhole cover & slab As per drawing & specification (submit the sample)	Set	1614.2	2500
140	Ratchet die set 1/2inch to 1inch (submit sample)	each	3238.4	5500
141	Ratchet die set 1 1/4inch to 2inch (submit sample)	each	6476.8	9500
142	Ratchet die set 3inch to 4inch (submit sample)	each	15249.6	18500
143	Rebar 10mm. TATA steel bars. IS - 1786/1985. Grade FE415. TOR	Kg	0	78
144	Rebar 6mm. TATA steel bars. Plain IS - 1786/1985. Grade FE415. TOR	Kg	0	78
145	Reflector jackets/safety jacket	each	126	650
146	Rod cutter blade 4inch (submit sample)	each	21	30
147	Safety Gloves	each	48	250
148	Safety Helmets (KARAM)	each	248	350
149	Stone chisel 1 1/2inch	each	720	750
150	Suunto Tandern Clinometer with precision compass 9 360 PC/360 R)	each	0	0
151	Teflon cover/bag	each	90	0
152	Thermochrome crayon	each	75	0
153	Tin cutter/snip	each	220.8	850
154	Trowel. masonry 2 inch x 5 inch	each	35.2	80
155	Trowel. masonry 4 inch x 8 inch	each	91.2	80
156	Vice 3inch (Bench)	each	3072	4500
157	Vice 6inch (Bench)	each	5164.8	7800
158	Wheel Bearing Grease. in 1/2 kg pot	Pot	416	0
159	Wire. GI binding Gauge 22 SWG. In roll of 1kg (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	kg	110.2	100

160	Wire. mesh chicken 23 SWG. hexagonal 15 mm. 11/2inch full twist. double string at side. width 1 metre. in rolls of 25 m (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	m	62.35	130
161	Wire.Plain Gauge 8 SWG with light galvanized coating. In rolls of 40 kg. weight tolerance of +3 kg. -0 kg. (BSB approved brands. need to submit the sample and manufacturer's certificate of origin)	Kg	85.55	120
162	Wrench slide 14inch (Ludra brand)	each	812.8	480
163	Wrench. pipe 12inch (Ludra brand)	each	348.8	600
164	Wrench. pipe 14inch (Ludra brand)	each	457	1250
165	Wrench. pipe 18inch (Ludra brand)	each	726.4	1600
166	Wrench. pipe 24inch (Ludra brand)	each	1318.4	2100
167	Wrench. pipe 36inch (Ludra brand)	each	2716.8	3500
168	Wrench. pipe 48inch (Ludra brand)	each	3190.4	4500

	Bidder Information	Mail address	Station
1	Druk General Enterprise	drukge467@gmail.com	Pling
2	Tenzin Norgyel Tshongkhang	tntshongkhang@gmail.com	Sjongkhar